

OAC Cabinet Specifications

Box Construction:

Face-frame made of birch wood; 1 1/2" wide x 3/4" thick

1/2" plywood carcass with half sliding dovetail joint and pocket screw assembly

Back panel of cabinets is 1/4" thick with 1/2" frame around the edges

3/4" thick plywood shelves with all four sides edge-banded

Natural color drawer boxes with dovetailed joints using poplar wood: 2 base coats with 1 top coat using all UV paint

6-ways adjustable and concealed European soft-close hinges for all doors are standard; except for Base Lazy Susan and Wall Easy Reach cabinets

Soft closing undermount glides with 6-way adjustable is standard on drawers; except for spice rack pull out, which has 2-way adjustable (up/down) undermount glides

Matching interiors to the exterior door color with 3 layers of paint; 2 base layers and 1 top coat using all UV paint

Metal L-brackets provided for base and upper cabinets; not the cheap plastic or wooden ones

Environmentally Friendly and Safe - California Phase 2 Compliant (CARB 2)

General Cabinet Specifications:

Doors and Drawer fronts are solid birch with 3/8" thick Medium Density Fiberboard (MDF) center panels to minimize expansion and contraction; which reduces the chance of joint cracks where the rails and stiles are jointed

Full overlay face-framed cabinets with a 1/4" reveal

The distance between the fronts is 1/4" apart

For double door cabinets, the gap between the doors is 1/8" apart

Regular base cabinets 30" wide and wider will have two drawers

Double door cabinets, uppers and lowers, come with doors pre-hung onto the face frame

Single door upper cabinets will have the door pre-hung onto the face frame

Single door base cabinets will **NOT** have the door pre-hung onto the face frame so it can be hinged as needed according to layout by assembler or installer

Base cabinets are 24" deep x 34 1/2" tall, and have a 3" recessed toe kick area

Regular upper cabinets are 12" deep

24" deep bridge cabinets are available

Vanity cabinets are 21" deep x 34 1/2" tall

9 Step Finishing Process:

Each of our door styles receive the best-in-class 9 step finishing process:

- 1: Machine and hand sanded and then vacuumed
- 2: Primer is applied
- 3: Oven-cured
- 4: Sanding
- 5: Base coating is applied
- 6: Oven dried
- 7: Sanding
- 8: Top coat is applied
- 9: Oven dried

General Notes:

Our base cabinets do not come with a toe kick. Please remember to order toe kick with each order. Toe kicks are 1/2" thick, 96" long, and 4 1/2" tall.

[xxx] = inches; the larger numbers above it are measured in millimeters

